

DATE : _____ SURFACE : _____ NOTE : _____

TRACK : _____ GRIP : _____

Caster

☐ 6°
☐ 8°
☐ 10°
☐ 12°

Steering

FRONT

Tire: _____

Wheel: _____

Offset: _____

REAR

Tire: _____

Wheel: _____

Offset: _____

Front upright

Front suspension

Camber: _____

Toe-in: _____

Ride height: _____ mm ↑ GROUND

Front Suspension mount Rollcenter

Front damper

Shock oil: _____

Spring: _____ mm

Spring color: _____

Piston: _____ mm

Piston hole: _____

Spur Gear ÷ Pinion Gear × Reduction Gear = Gear ratio

_____ T ÷ _____ T × _____ = _____

Motor & ESC: _____ Battery: _____

Transceiver: _____ Gyro: _____ Sensitivity: _____

☐ Servo

☐ Battery

Centered

☐ Centered low gravity

☐ Centered upper motor

Rear diff

☐ Spool

☐ Ball diff.

Rear suspension

Camber: _____

Toe-in: _____

Ride height: _____ mm

Rear upright

Rear Suspension mount Rollcenter

Rear damper

Shock oil: _____

Spring: _____ mm

Spring color: _____

Piston: _____ mm

Piston hole: _____

2nd Reduction Gear

- ☐ 32T / 18T - 1.78 ☐ 40T / 16T - 2.50
- ☐ 34T / 18T - 1.89 ☐ 40T / 13T - 3.08
- ☐ 36T / 17T - 2.12 ☐ 42T / 11T - 3.82

※ Please download the blank setup sheet at [www.rc-mst.com].